## **R105**

## **SKID LOADERS**



GEHL.

			K 103 - Created Off February 9, 2022 at 1.34.31 FM C
Capacities		Metric	Imperial
Rated Operating Capacity		476 kg	1049 lbs
Rated Operating Capacity with Optional Counterweight		533 kg	1175 lbs
Unladen weight		1905 kg	4200 lbs
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3607 mm	142 in
Height to Hinge Pin – Fully Raised	h28	2731 mm	108 in
Overall Height to Top of ROPS	h17	1784 mm	70 in
Dump angle at full height	a5	40 °	40 °
Dump height	h29	2083 mm	82 in
Overall length with bucket	l16	2997 mm	118 in
Dump reach - Full height		641 mm	25 in
Rollback at ground		31°	31°
Seat to ground height	h30	826 mm	33 in
Wheelbase	у	876 mm	34 in
Overall width less bucket	b1	1232 mm	49 in
Bucket Width	e1	1372 mm	54 in
Ground clearance	m4	159 mm	6 in
Overall length - Less Bucket	l2	2248 mm	89 in
Clearance Radius - Front with Bucket	b18	1829 mm	72 in
Clearance Circle - Front without Bucket	b19	1067 mm	42 in
Clearance Circle - Rear	wa1	1372 mm	54 in
Performances		·	
Travel speed (unladen)		8.26 km/h	5 mph
Wheels		·	·
Standard tyres		27x8.5x15 HD	27x8.5x15 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		3TNV88C-KMSV Stage V	3TNV88C-KMSV Stage V
Engine norm		Stage V	Stage V
Gross Power (kW)		25.50 kW	25.50 kW
Net Power (kW)		23.70 kW	23.70 kW
Max. torque / Engine rotation		109.40 Nm / 2800 rpm	109.40 Nm / 2800 rpm
Battery		12 V	12 V
Starter (kW)		2.30 kW	2.30 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		55 l/min	55 l/min
Tank capacities			11.4
Fuel tank		37.90 l	10 US gal
Reservoir Capacity Hydraulics		30.30 L	8 US gal
Displacement		1.64 l	0 US gal
Noise and vibration			
Environmental noise (LwA)		101 dB(A)	101 dB(A)
Whole-Body Vibration (ISO 2631-1)		1.12 m/s <sup>2</sup>	1.12 m/s <sup>2</sup>





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399

euros - 857 802 508 RCS West Bend